



# SRK20ZS-W / SRC20ZS-W

2.0(0.9~2.9)

Indoor Unit : SRK20ZS-W

Outdoor Unit : SRC20ZS-W

## Specifications






Indoor unit		SRK20ZS-W	
Outdoor unit		SRC20ZS-W	
Power source		1Phase, 220 - 240, 50Hz	
Nominal cooling capacity (Min~Max)		kW	2.0(0.9~2.9)
Nominal heating capacity (Min~Max)		kW	2.7(0.9~4.3)
Power consumption	Cooling/Heating	kW	0.44 / 0.59
EER/COP	Cooling/Heating		4.55 / 4.58
Max. running current		A	9
Sound power level	Indoor	Cooling/Heating	48 / 50
	Outdoor	Cooling/Heating	56 / 56
Sound pressure level	Indoor	Cooling (Hi/Me/Lo/Ulo)	dB(A) 34 / 25 / 22 / 19
		Heating (Hi/Me/Lo/Ulo)	
	Outdoor	Cooling/Heating	45 / 45
Air flow	Indoor	Cooling (Hi/Me/Lo/Ulo)	m3/min 9.3 / 7.0 / 5.9 / 5.0
		Heating (Hi/Me/Lo/Ulo)	
	Outdoor	Cooling/Heating	27.4 / 23.6
Exterior Dimensions	Indoor	Height x Width x Depth	mm
	Outdoor		
Net weight	Indoor / Outdoor	kg	9.5 / 31.0
Refrigerant	Type/GWP		R32 / 675
Refrigerant	Charge	kg/TCO2Eq	0.62 / 0.419
Refrigerant piping size	Liquid/Gas	mm (ø inch)	6.35(1/4") / 9.52(3/8")
Refrigerant line (one way) length		m	Max. 20
Vertical height differences	Outdoor is higher/lower	m	Max. 10 / Max. 10
Outdoor operating temperature range	Cooling	°C	-15~46
	Heating		-15~24
Clean filter		Allergen Clear Filter x 1, Photocatalytic Washable Deodorizing Filter x 1	
Energy Class (Cooling/Heating)		A+++ / A++	
SEER		10.00	
SCOP (Average climate)		8.5	
Pdesign (cooling/heating(@-10°C))		kW	2.00/2.60
Annual Electricity Consumption (cooling/heating)		kWh/a	83/793
Designated Heating Season		Average	

- The data is measured under the following conditions(ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.
- Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.
- 'tonne(s) of CO2 equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.
- SEER/SCOP are based on EN14825:2016 and Commission regulation (EU) No.2016/2281




## Schematics

**SRK20ZS-W,-WB,-WT SRK25ZS-W,-WB,-WT  
SRK35ZS-W,-WB,-WT SRK50ZS-W,-WB,-WT  
SRK20ZS-S,-SB,-ST SRK25ZS-S,-SB,-ST  
SRK35ZS-S,-SB,-ST SRK50ZS-S,-SB,-ST**



Symbol	Content
A	Gas piping SRK20, 25, 35 $\phi$ 9.52 (3/8") (Flare) SRK50 $\phi$ 12.7 (1/2") (Flare)
B	Liquid piping $\phi$ 6.35 (1/4") (Flare)
C	Hole on wall for right rear piping ( $\phi$ 65)
D	Hole on wall for left rear piping ( $\phi$ 55)
E	Drain hose VP16
F	Outlet for piping (on both side)

**SRC20ZS-W SRC25ZS-W SRC35ZS-W  
SRC20ZS-S SRC25ZS-S SRC35ZS-S**



Symbol	Content
A	Service valve connection (gas side) $\phi$ 9.52 (3/8") (Flare)
B	Service valve connection (liquid side) $\phi$ 6.35 (1/4") (Flare)
C	Pipe/cable draw-out hole
D	Drain discharge hole $\phi$ 20x2places
E	Anchor bolt hole M10x4places

Examples of installation Dimensions	Minimum installation space			
	I	II	III	IV
L1	Open	280	280	180
L2	100	75	Open	Open
L3	100	80	80	80
L4	250	Open	250	Open

